

1 4. The eye patch of claim 1, wherein
2 the body is adapted to at least partially extend along the side arm.

1 5. The eye patch of claim 1, wherein the first fastener comprises a loop comprising a
2 first end secured to the body and a second end adapted to extend around the bridge to releasably
3 couple the bridge to the body.

1 6. The eye patch of claim 5, wherein the first fastener further comprises:
2 a releasable connector adapted to releasably couple the side arm to the body.

a1

1 7. The eye patch of claim 5, wherein
2 the body includes at least one slot, and
3 the second end comprises a pronged tab adapted to be inserted into the slot to releasably
4 couple the second end to the body.

1 8. The eye patch of claim 1, wherein the second fastener comprises at least one slit
2 formed in the body to receive the arm.

1 9. The eye patch of claim 1, wherein the second fastener comprises:
2 a loop adapted to extend around the side arm, the loop having a first end secured to the
3 body and a second end.

1 10. The eye patch of claim 9, wherein the second end is adapted to releasably couple
2 the loop to the body.

1 11. The eye patch of claim 9, wherein the second end is secured to the body.

1 12. The eye patch of claim 1, wherein the body comprises a fabric selected from a set
2 consisting essentially of: fabric and foam.

1 13. The eye patch of claim 1, wherein the body comprises a pliable material.

1 14. The eye patch of claim 1, wherein the first fastener is adapted to attach the body to
2 the bridge regardless of whether the eye comprises a left eye or a right eye.

1 15. The eye patch of claim 1, wherein the second fastener is adapted to attach the
2 body to the arm regardless of whether the eye comprises a left eye or a right eye.

1 16. An assembly comprising:
2 eyeglass frames comprising a bridge and a side arm; and
3 an eye patch comprising:
4 a flexible body to be positioned on a front of the frames to substantially block both frontal
5 and peripheral vision of an eye;
6 a first fastener to attach the body to the bridge of the eyeglass frames; and
7 a second fastener to attach the body to the arm of the eyeglass frames.

1 17. The assembly of claim 16, wherein
2 the eyeglass frames comprises a lens socket, and
3 the body is adapted to at least partially extend over the lens socket.

1 18. The assembly of claim 16, wherein
2 the body is adapted to at least partially extend along the side arm.

1 19. The assembly of claim 16, wherein the first fastener comprises a loop comprising
2 a first end secured to the body and a second end adapted to extend around the bridge to releasably
3 couple the bridge to the body.

1 20. The assembly of claim 19, wherein the first fastener further comprises:
2 a releasable connector adapted to releasably couple the side arm to the body.

1 21. The assembly of claim 19, wherein
2 the body includes at least one slot, and
3 the second end comprises a pronged tab adapted to be inserted into the slot to releasably
4 couple the second end to the body.

1 22. The assembly of claim 16, wherein the second fastener comprises at least one slot
2 formed in the body to receive the side arm.

1 23. The assembly of claim 16, wherein the second fastener comprises:
2 a loop adapted to extend around the side arm, the loop having a first end secured to the
3 body and a second end.

1 24. The assembly of claim 23, wherein the second end is adapted to releasably couple
2 the loop to the body.

1 25. The assembly of claim 23, wherein the second end is secured to the body.

1 26. The assembly of claim 16, wherein the body comprises a fabric selected from a set
2 consisting essentially of: fabric and foam.

1 27. The assembly of claim 16, wherein the body comprises a fabric selected from a
2 pliable material.

1 28. The assembly claim 16, wherein the first fastener is adapted to attach the body to
2 the bridge regardless of whether the eye comprises a left eye or a right eye.

1 29. The assembly of claim 16, wherein the second fastener is adapted to attach the
2 body to the side arm regardless of whether the eye comprises a left eye or a right eye.

1 30. (Amended) An eye patch usable with eyeglass frames, comprising:
2 a flexible body to be fastened to at least partially cover a front of the eyeglass frames to
3 substantially block both frontal and peripheral vision of an eye; and
4 at least one fastener to secure the flexible body to the frames.

Sub B27
2 31. The eye patch of claim 30, wherein
3 the eyeglass frames comprises a lens socket, and
4 the body is adapted to at least partially extend over the lens socket.

1 32. The eye patch of claim 30, wherein
2 the body is adapted to at least partially extend along a side arm of the frames.

Q1
Sub B37
2 33. The eye patch of claim 30, wherein
3 the eyeglass frames comprise a side arm and a bridge, and
4 at least one fastener comprises:
5 a first fastener to attach the eye patch to the bridge; and
6 a second fastener to attach the eye patch to the side arm.

1 34. (Amended) An assembly comprising:
2 eyeglass frames; and
3 an eye patch comprising:
4 a flexible body to be fastened to at least partially cover a front of the eyeglass
5 frames to substantially block both frontal and peripheral vision of an eye; and
6 at least one fastener to secure the flexible body to the frames.

1 35. The assembly of claim 34, wherein
2 the eyeglass frames comprises a lens socket, and
3 the body is adapted to at least partially extend over the lens socket.

1 36. The assembly of claim 34, wherein
2 the eyeglass frames holds a lens, and
3 the body is adapted to at least partially extend over the lens.

1 37. The assembly of claim 34, wherein
2 the body is adapted to at least partially extend along a side arm of the frames.

1 38. The assembly of claim 34, wherein
2 the eyeglass frames comprise a side arm and a bridge, and
3 said at least one fastener comprises:
4 a first fastener to attach the eye patch to the bridge; and
5 a second fastener to attach the eye patch to the side arm.

a1

1 39. (New) An eye patch usable with eyeglass frames that comprises a bridge, the eye
2 patch comprising:
3 a flexible body to be positioned on a front of the frames to substantially block both frontal
4 and peripheral vision of an eye; and
5 a fastener extending from the body to attach the body to the bridge.

a2
[Handwritten scribbles]

1 40. (New) The eye patch of claim 39, wherein
2 the body is adapted to at least partially extend along a side arm of the frames.

1 41. (New) The eye patch of claim 39, wherein the flexible body is not positioned on a
2 rear of the frames.

1 42. (New) The eye patch of claim 39, wherein the fastener comprises a tab separate
2 from the body to secure the body of the bridge of the frame.